



ARRI ALEXA Classic

Electronic Viewfinder (EVF-1 & Eyecup)
Highspeed Licence

Alexa accessories

Viewfinder Mounting Bracket
Viewfinder Extension Bracket
Short Viewfinder Cable
Medium Viewfinder Cable
Centre Camera Handle
Handle Extension Bracket
V-Lock Battery Adaptor
1 x 24v Camera / Battery Cable
Power supply unit (mains)
BP-12 Bridge Plate
Bridge plate Adaptor
Balance Plate
Pair of 19mm / 440mm Bars (Long)
Pair of 19mm / 240mm Bars (Short)
Pair of 15mm Lightweight Bars - Short 240mm
Shoulder Pad
Hand Held unit on/off handle
Levelling Block
2 x Allen Key
Articulate arm



Media

5 x Sony SBP-32GB SxS Memory Card
3 x Sony SBP-64GB SxS Memory Card
SxS Pro card reader



Power supply

Bebob Hot swap adaptor
Battery pack for Alexa 30V 5.5 Hours
2 x Red Chargers
4 X Red Bricks Batteries
BEBOB Battery V140RM



Monitors

SONY Monitor LMD-2050W (calibrated)
Sun Shader
7" iKAn VX7i-S field on board monitor
Batteries – shader – articulating arm with clamp
LG 24" Client monitor
SDI to HDMI converter
Power supply + BNC Cables



Support

Tripod Head
Sachtler CINE 30 HD Head
(Sachtler mount plate
Sachtler side handle)
Sachtler fibercarbon legs
Hand Held Unit
Hi - Hat



Recorder - Monitor

ATOMOS SAMURAI
HD Monitor Transcoder DNxHD
4 Batteries Charger
Hard Disk Up-Down Loader



Lenses

ARRI Master Primes 1.3

16mm-25mm-35mm-50mm-75mm



ARRI Zeiss High Speed 1,4

18mm-25mm-35mm-50mm-85mm-135mm



Schneider Xenon

100mm T 2,1



Cooke Zoom lens

25-250mm T 3,8



RED ZOOM

18mm – 50mm T 3



RED TELE

300mm T 2,9



DUCLOS ZOOM

11mm- 16mm T 2,8



Follow focus

CINEVATE Follow Focus 19mm
Clip on follow focus 15mm/19mm
TILTA Follow focus



Remote

Air Wireless Follow Focus system



Matte box

ARRI Lightweight Matte Box LMB-25

3 filter stage 4 x 5.65



Studio Redrockmicro Matte box

(2 x side doors, 1 x Top door, Matte mount x 2


Back lens light protectors x 5)



Filters

rsND Filter 4 x 5.6 (0.6 Micro, 0.9 Cavision, 1.2 Cavision,
Polariz Micro, Grated ND Micro.
4x5,65 PrimeCircle IRND X-FS Extended full spectrum Set 5: 0.3 –
0.6 – 0.9 – 1.2 – 1.5

PrimeCircle Filters Clear Optical Flat)



Paralinx Plus

Uncompressed 4:2:2 1920x1080 10-bit video. Less than 1ms
latency. Supports multiple framerates and resolutions.

Range of over 300ft (91m) line-of-sight. HDMI video input/
output. Plug & Play--no set-up required.

Supported framerates: 23.98p, 24p, 25p, 29.97p, 30p, 50i, 50p,

59.94i, 60i, 60p

